

# Oertzen HDL 200



## **OERTZEN High Pressure Fire Extinguisher HDL 200**

Hp fire extinguishing installation model with 100 l tank  
solid, surrounding steel frame (powder coated) with 4 rubber/metal  
bumpers  
1 cyl./ 4 stroke petrol engine (heavy duty) 9.6 kW/13 hp  
with oil pressure control and recoil rope starter  
petrol tank 5 l (canister)  
reduction gearbox (pump rpm 1450 1/min)  
3 cyl. inline plunger pump 22 l/min (splash oil lubricated) forged  
crankshaft  
wear-free ceramic plungers, forged brass cylinder head, stainless steel  
valves  
foam agent injection (3 %) with stop valve  
thermo valve (prevents overheating)  
pressure relief for pump by hp unloader valve with extinguishing pistol  
closed

### **Standard equipment:**

60 m JET hp extinguishing hose (300 bar) on hose reel with swivel  
joint  
crank and brake, hose swivel, lockable extinguishing pistol  
DUPLEX rapid attack attachment for spray and low expansion foam  
(simply by turning DUPLEX attachment)

Order-number: 10.000.777

<b>Technical characteristics</b>	
Dimensions	760 x 670 x 840 mm
Weight	99 kg (with tank)
Engine/motor	4-stroke petrol engine, 1 cyl. 9.6 kW
Start	recoil rope starter
HP plunger pump	3 cyl. 22 l/min
Extinguishing pressure max.	200 bar
HP hose	60 m (300 bar)
Water tank	100 l
Foam agent injection	standard
Extinguishing pistol	DUPLEX Attachment