

Oertzen HDL 250



OERTZEN High Pressure Fire Extinguisher HDL 250

Hp fire extinguishing installation model without tank
solid, surrounding steel frame (powder coated) with 4 rubber/metal
bumpers
2 cyl./ 4 stroke petrol engine (heavy duty) 13.2 kW/18 hp
with oil pressure control, electric and recoil rope starter
petrol tank 5 l (canister)
reduction gearbox (pump rpm 1450 1/min)
3 cyl. inline plunger pump 23 l/min (splash oil lubricated) forged
crankshaft
wear-free ceramic plungers, forged brass cylinder head, stainless steel
valves
foam agent injection (3 %) with stop valve
thermo valve (prevents overheating)
pressure relief for pump by hp unloader valve with extinguishing pistol
closed

Standard equipment:

60 m PANZERJET hp extinguishing hose (500 bar) on hose reel with
swivel joint, crank and brake, hose swivel, lockable extinguishing
pistol, DUPLEX rapid attack attachment for spray and low expansion
foam
(simply by turning DUPLEX attachment)

Option: MEDIJET hp extinguishing hose 60 m, easy coil, super even
and fire-proof,
is mounted instead of the standard PANZERJET high pressure hose if
desired.

Order-number: 10.000.997

Technical characteristics

Dimensions	980 x 560 x 560 mm
Weight	138 kg (without tank)
Engine/motor	4-stroke petrol engine, 2 cyl. 13.2 kW
Start	electric / recoil rope starter
HP plunger pump	3 cyl. 23 l/min
Extinguishing pressure max.	250 bar
HP hose	60 m (500 bar)
Water tank	-
Foam agent injection	standard
Extinguishing pistol	DUPLEX Attachment