

Oertzen HDL 250 D



OERTZEN High Pressure Fire Extinguisher HDL 250 D

Hp fire extinguishing installation model without tank
solid, surrounding steel frame (powder coated) with 4 rubber/metal bumpers
1 cyl./ 4 stroke diesel engine (heavy duty) 7.5 kW/10 hp
with oil pressure control and recoil rope starter
diesel tank 5.5 l (canister)
reduction gearbox (pump rpm 1450 1/min)
3 cyl. inline plunger pump 23 l/min (splash oil lubricated) forged crankshaft
wear-free ceramic plungers, forged brass cylinder head, stainless steel valves
foam agent injection (3 %) with stop valve
thermo valve (prevents overheating)
pressure relief for pump by hp unloader valve with extinguishing pistol
closed



Standard equipment:

60 m PANZERJET hp extinguishing hose (500 bar) on hp hose reel with hp
swivel joint, crank and brake, hose swivel, lockable extinguishing pistol,
DUPLEX rapid attack attachment for spray and low expansion foam
(simply by turning DUPLEX attachment)

Option: MEDIJET hp extinguishing hose 60 m, easy coil, super even and
fire-proof, is mounted instead of the standard PANZERJET high pressure
hose if desired.

Illustr. shows accessory 125 l-tank and extra equipment wheel-kit

next illustration:

**HDL 250 D with extra equipment 100 m extinguishing hose and electric
hose reel drive**

Order-number: 10.000.984

Technical characteristics

Dimensions	1090 x 560 x 560 mm
Weight	147 kg (without tank)
Engine/motor	4-stroke diesel engine, 2 cyl. 7.5 kW
Start	recoil rope starter
HP plunger pump	3 cyl. 23 l/min
Extinguishing pressure max.	180 bar
HP hose	60 m (500 bar)
Water tank	-
Foam agent injection	standard
Extinguishing pistol	DUPLEX Attachment