

# Oertzen HDL 250 32, 75 m



## **OERTZEN High Pressure Fire Extinguisher HDL 250-32, 75 m hose**

Hp fire extinguishing installation model without tank  
solid, surrounding steel frame (powder coated) with 4 rubber/metal bumpers

2 cyl./ 4 stroke petrol engine (heavy duty) 13.2 kW/18 hp  
with oil pressure control, electric and recoil rope starter

petrol tank 5 l (canister)

reduction gearbox (pump rpm 1450 1/min)

3 cyl. inline plunger pump 32 l/min (splash oil lubricated) forged crankshaft

wear-free ceramic plungers, forged brass cylinder head, stainless steel valves

foam agent injection (3 %) with stop valve

thermo valve (prevents overheating)

pressure relief for pump by hp unloader valve with extinguishing pistol closed

### **Standard equipment:**

75 m high pressure extinguishing hose (500 bar) on hose reel with swivel joint, crank and brake, hose swivel

lockable extinguishing pistol rapid attack DUPLEX attachment for spray and low expansion foam

(simply by turning DUPLEX attachment)

### **Illustr. shows accessory electric hose reel drive and TRIPLEX attachment**

Order-number: 10.000.678

#### **Technical characteristics**

Dimensions	1150 x 560 x 560 mm
Weight	148 kg (without tank)
Engine/motor	4-stroke petrol engine, 2 cyl. 13.2 kW
Start	electric / recoil rope starter
HP plunger pump	3 cyl. 32 l/min
Extinguishing pressure max.	200 bar
HP hose	75 m (500 bar)
Water tank	-
Foam agent injection	standard
Extinguishing pistol	DUPLEX Attachment