

Oertzen HDL 250 E



OERTZEN High Pressure Fire Extinguisher HDL 250 E

Hp fire extinguishing installation model without tank
solid, surrounding steel frame (powder coated) with 4 rubber/metal
bumpers
electric motor (heavy duty) 8.9 kW
3 cyl. inline plunger pump 23 l/min (splash oil lubricated) forged
crankshaft
wear-free ceramic plungers, forged brass cylinder head, stainless steel
valves
foam agent injection (3 %) with stop valve
thermo valve (prevents overheating)
pressure relief for pump by hp unloader valve with extinguishing pistol
closed

Standard equipment:

60 m PANZERJET hp extinguishing hose (500 bar) on hp hose reel with
hp swivel joint, crank and brake, hose swivel, lockable extinguishing
pistol, DUPLEX rapid attack attachment for spray and low expansion
foam
(simply by turning DUPLEX attachment)

Option: MEDIJET hp extinguishing hose 60 m, easy coil, super even and
fire-proof, is mounted instead of the standard PANZERJET high pressure
hose if desired.

Illustr. shows accessories 125 l tank and wheel-kit

Order-number: 10.000.993

Technical characteristics

Dimensions	980 x 560 x 560 mm
Weight	127 kg (without tank)
Engine/motor	electric motor 400 V/50 Hz, 8.9 KW
Start	ON/OFF- switch
HP plunger pump	3 cyl. 23 l/min
Extinguishing pressure max.	220 bar
HP hose	60 m (500 bar)
Water tank	-
Foam agent injection	standard
Extinguishing pistol	DUPLEX Attachment