

Oertzen HDL 200 utan tank



OERTZEN High Pressure Fire Extinguisher HDL 200 without tank

Hp fire extinguishing installation model built on solid steel platform (powder coated) with 4 rubber/metal bumpers

1 cyl./ 4 stroke petrol engine (heavy duty) 9.6 kW/13 hp

with oil pressure control and recoil rope starter

petrol tank 5 l (canister)

reduction gearbox (pump rpm 1450 1/min)

3 cyl. inline plunger pump 22 l/min (splash oil lubricated) forged crankshaft

wear-free ceramic plungers, forged brass cylinder head, stainless steel valves

foam agent injection (3 %) with stop valve

thermo valve (prevents overheating)

pressure relief for pump by hp unloader valve with extinguishing pistol closed

Standard equipment:

60 m JET hp extinguishing hose (300 bar) on hose reel with swivel joint

crank and brake, hose swivel, lockable extinguishing pistol

DUPLEX rapid attack attachment for spray and low expansion foam (simply by turning DUPLEX attachment)

Order-number: 10.000.778

Technical characteristics

Dimensions	760 x 670 x 520 mm
Weight	82 kg (without tank)
Engine/motor	4-stroke petrol engine, 1 cyl. 9.6 kW
Start	recoil rope starter
HP plunger pump	3 cyl. 22 l/min
Extinguishing pressure max.	200 bar
HP hose	60 m (300 bar)
Water tank	100 l
Foam agent injection	serially
Extinguishing pistol	DUPLEX Attachment