

# Oertzen HDL 250 32



## **OERTZEN High Pressure Fire Extinguisher HDL 250-32**

Hp fire extinguishing installation model without tank  
solid, surrounding steel frame (powder coated) with 4 rubber/metal  
bumpers  
2 cyl./ 4 stroke petrol engine (heavy duty) 13.2 kW/18 hp  
with oil pressure control, electric and recoil rope starter  
petrol tank 5 l (canister)  
reduction gearbox (pump rpm 1450 1/min)  
3 cyl. inline plunger pump 32 l/min (splash oil lubricated) forged  
crankshaft  
wear-free ceramic plungers, forged brass cylinder head, stainless steel  
valves  
foam agent injection (3 %) with stop valve  
thermo valve (prevents overheating)  
pressure relief for pump by hp unloader valve with extinguishing pistol  
closed

### **Standard equipment:**

50 m hp extinguishing hose (500 bar) on hose reel with swivel joint, crank  
and brake, hose swivel  
lockable extinguishing pistol, DUPLEX rapid attack attachment for spray  
and low expansion foam  
(simply by turning DUPLEX attachment)

### **pic. HDL 250-32 with 175 l tank (option)**

Order-number: 10.000.673

### **Technical characteristics**

Dimensions	980 x 580 x 560 mm
Weight	138 kg (without tank)
Engine/motor	4-stroke petrol engine, 2 cyl. 13.2 kW
Start	electric / recoil rope starter
HP plunger pump	3 cyl. 32 l/min
Extinguishing pressure max.	200 bar
HP hose	50 m (500 bar)
Water tank	-
Foam agent injection	standard
Extinguishing pistol	DUPLEX Attachment