

# Oertzen HDL 250, mobile, 100 m



## **OERTZEN High Pressure Fire Extinguisher HDL 250, mobile, 100 m hose**

Hp fire extinguishing model without tank

solid, surrounding steel frame (powder coated)

chassis with 2 wheels, 2 swivel pulleys with locking brake and push bar

2 cyl./ 4 stroke petrol engine (heavy duty) 13.2 kW/18 hp

with oil pressure control, electric and recoil rope starter

petrol tank 5 l (canister)

reduction gearbox (pump rpm 1450 1/min)

3 cyl. inline plunger pump 23 l/min (splash oil lubricated) forged crankshaft

wear-free ceramic plungers, forged brass cylinder head, stainless steel valves

foam agent injection (3 %) with stop valve

thermo valve (prevents overheating)

pressure relief for pump by hp unloader valve with extinguishing pistol closed

### **Standard equipment:**

100 m PANZERJET hp extinguishing hose (500 bar) on hose reel with swivel joint, crank and brake, hose swivel,

lockable extinguishing pistol rapid attack DUPLEX attachment for spray and low expansion foam

(simply by turning DUPLEX attachment)

**Option:** MEDIJET hp extinguishing hose 100 m, easy coil, super even and fire-proof, is mounted instead of the standard PANZERJET high pressure hose if desired.

### **Illustr. shows accessory 125 l tank**

Order-number: 10.000.677

### **Technical characteristics**

Dimensions	1360 x 760 x 1,110 mm
Weight	204 kg (with tank)
Engine/motor	4-stroke petrol engine, 2 cyl. 13.2 kW
Start	electric / recoil rope starter
HP plunger pump	3 cyl. 23 l/min
Extinguishing pressure max.	250 bar
HP hose	100 m (500 bar)
Water tank	125 l
Foam agent injection	standard
Extinguishing pistol	DUPLEX Attachment